1,2-SBS-L42

1,2-SBS-L42	含有比 (wt%) o/p/q	Mn	1,2-ビニル (%) m/(m+n)	粘度 (P@45℃)
液状	10/80/10	4,500	≥80	1200

参考值

溶解件



溶媒	1,2-SBS-L42			
冶炼	10wt%	50wt%		
Toluene	S	S		
MEK	S	S		

液状

1,2-SBSに含まれる1,2-ビニル基は、 架橋によって物性改善をもたらします。

サンプル供試可能

問合せ: info@nissogr.com

S: 溶解

The information described in this sheet is believed to be accurate and is presented in good faith with no guarantee or obligation as to accuracy and no $assumption\ of\ liability.\ Users\ should\ make\ their\ own\ tests\ to\ determine\ the\ suitability\ of\ products\ for\ their\ own\ particular\ use.\ NISSO\ makes\ no\ particular\ use.$ warranty of any kind, express or implied, including those of merchantability and fitness for particular purpose other than the material conforms to its applicable current standard specifications.

1,2-SBS-P35

1,2-SBS-P35	含有比 (wt%) o/p/q	Mn	1,2-ビニル (%) m/(m+n)	粘度 (P@45℃)
固形	25/50/25	35,000	≥80	-

参考值



溶解件

溶媒	1,2-SBS-P35			
冶炼	10wt%	50wt%		
Toluene	S	S		
MEK	S	S		

S: 溶解

固形

1,2-SBSに含まれる1,2-ビニル基は、 架橋によって物性改善をもたらします。

サンプル供試可能

問合せ: info@nissogr.com

The information described in this sheet is believed to be accurate and is presented in good faith with no guarantee or obligation as to accuracy and no $assumption\ of\ liability.\ Users\ should\ make\ their\ own\ tests\ to\ determine\ the\ suitability\ of\ products\ for\ their\ own\ particular\ use.\ NISSO\ makes\ no\ particular\ use.$ warranty of any kind, express or implied, including those of merchantability and fitness for particular purpose other than the material conforms to its applicable current standard specifications.